MOVABLE BRASS CONTACT: Extends for connection to 2nd circuit in Advent Lytespan Track

POLARITY KEYWAY

7 3/4"



6 1/4"

SOCKET COVER:

1/4" 4

6

LYTESPAN ATTACHMENT FITTING: Molded polycarbanate; integral color; fitter twists anto track and locks on PUSH TAB: Molded polycarbonate; detaches unit PIVOT MOUNTING: Tansioned; 350" stop YDKE: 3/4" x .070 Steel

TENSION SPRING WASHER

1/Z" x .050" Steel

Catalog	Mounting	Finish	Lamp
9023WH	All Lytespan Track Systems	Matte White	75W PAR30 (Tungsten Halogen)
9023BK		Matte Black	

General Description

Minimal, functional form with cleanly detailed yoke and ring-shaped lampholder. Front relamping for easy maintenance. Units adjust horizontally up to 350,° vertically up to 90.°

Finish

All painted finishes baked enamel.

Electrical

Porcelain socket, medium base, nickel plated screw shell. No. 18 braided SF-1 leads with silicon sleeving.

Labels

U.L.; I.B.E.W.

Job Information	Туре:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710 We reserve the right to change details of design, materials and finish. www.lightolier.com © 2010 Philips Group • B0510

PHILIPS LIGHTOLIER®