

NVENT CADDY ROD LOCK CHANNEL NUT





CERTIFICATIONS



FEATURES

Provides fast universal attachment of threaded rod and hardware to standard strut profiles


Can be used to prefabricate assemblies which can be quickly pushed onto previously installed threaded rods


Works with slightly damaged threads and minor burrs on the threaded rod


SPECIFICATIONS

Catalog Number	Material	Finish	Rod Size(RS)	A	В	С	D	Static Load(F)	Packing Quantity
CRLS37EG	Cast Iron	Electrogalvanized	3/8"	0.910"	1.400"	0.769"	0.530"	750 lb	1.0000

DIAGRAMS







WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 - Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF

nVent.com
TRACER