



CONCRETE ANCHOR SCREW



FEATURES

For use with screw drill bits

ICC® approved for use in cracked and uncracked concrete

Meets NFPA® 13 as pre-qualified for seismic applications


SPECIFICATIONS

Finish: Electrogalvanized

Material: Steel

Catalog Number	Screw Diameter(Sc)	Screw Length(L)	A	Drill Bit Diameter	Embedment Depth	Torque(TQ)
CSBCAS025037EG	3/8"	2 1/2"	1/2"	3/8"	2" Min	245 ft lb
CSBCAS030050EG	1/2"	3"	1/2"	1/2"	2.50" Min	300 ft lb
CSBCAS040050EG	1/2"	4"	1"	1/2"	3" Min	300 ft lb
CSBCAS050050EG	1/2"	5"	3/4"	1/2"	4.25" Min	300 ft lb
CSBCAS040062EG	5/8"	4"	3/4"	5/8"	3.25" Min	350 ft lb
CSBCAS050062EG	5/8"	5"	1"	5/8"	4" Min	350 ft lb
CSBCAS050075EG	3/4"	5"	3/4"	3/4"	4.25" Min	400 ft lb

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER

© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.