

EMT Connectors

Compression Type - Steel

Features

- Compression type connectors
- Concrete tight
- Assembled with a steel locknut
- Also available with insulated throat

Applications

- Connectors: Use to join EMT to box or enclosure
- Couplings: Use to join two lengths of EMT

Standard Material

- Steel


Standard Finish

- Zinc plated



1/2"-2" E18472
2-1/2"-4" E148716

UL Standard: 514B
Fed. Spec. W-F-408E
NEMA: FB 1



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches		
						A	B	C
651S	16790	1/2"	25	250	30	1.750	1.250	.406
652S	16800	3/4"	25	250	43	1.813	1.563	.406
653S	16810	1"	10	100	25	2.000	1.813	.406
654S	16820	1-1/4"	---	25	12	2.750	2.188	.500
655S	16830	1-1/2"	---	20	12	3.000	2.438	.500
656S	16840	2"	---	15	15	3.188	2.938	.688
657S	16841	2-1/2"	---	12	19	3.875	3.688	.750
658S	16842	3"	---	6	15	4.375	4.313	.938
659S	16843	3-1/2"	---	6	16	4.500	4.875	.938
660S	16844	4"	---	6	21	4.750	5.375	.938