

Rigid Conduit Bodies

Threaded C Type

Features

- Threaded C type
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications


- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast

Standard Finish

- Powder coat



Catalog Number	UPC	Size	Max. Number	Wire Size	Unit Carton	Ship Case	Weight/Case	Inches		
				Max. Size				A	B	C
C1	19900	1/2"	1	6 AWG	10	100	24	4.720	1.370	1.330
C2	19910	3/4"	2	6 AWG	10	50	21	5.570	1.625	1.540
C3	19920	1"	3	6 AWG	5	25	15	6.460	1.900	1.740
C4	19930	1-1/4"	3	2 AWG	2	10	15	8.528	2.770	2.490
C5	19940	1-1/2"	3	2 AWG	2	10	17	8.528	2.770	2.490
C6	19950	2"	3	2/O AWG	5	5	13	10.831	3.335	3.100
C7	19960	2-1/2"	3	4/O AWG	---	1	6	13.500	4.060	4.450
C8	19970	3"	3	250 MCM	---	1	6	13.000	4.685	4.450
C9	19980	3-1/2"	3	350 MCM	---	1	8	15.937	5.450	5.500
C10	19990	4"	4	350 MCM	---	1	8	15.937	5.450	5.500