


Rigid Conduit Bodies

Threaded LB Type



E195124

UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1

Features

- Threaded LB type
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Copper free aluminum die cast

Standard Finish

- Powder coat

Catalog Number	UPC	Size	Wire Size		Unit Carton	Ship Case	Weight/Case	A	B	C
			Max. Number	Max. Size						
LB1	20840	1/2"	1	6 AWG	10	100	28	4.295	2.15	1.33
LB2	20850	3/4"	2	6 AWG	10	50	19	5.09	2.43	1.54
LB3	20860	1"	3	6 AWG	5	25	18	5.915	2.765	1.74
LB4	20870	1-1/4"	3	2 AWG	2	10	13	7.894	3.665	2.49
LB5	20880	1-1/2"	3	2 AWG	2	10	14	7.894	3.665	2.49
LB6	20890	2"	3	2/O AWG	1	5	13	10.134	4.275	3.10
LB7	20900	2-1/2"	3	2/O AWG	---	1	3	12.50	5.437	4.45
LB8	20910	3"	3	4/O AWG	---	1	4	12.50	5.675	4.45
LB9	20920	3-1/2"	3	400 MCM	---	1	7	15.50	6.922	5.50
LB10	20930	4"	3	400 MCM	---	1	7	15.50	6.922	5.50

Threaded C Type



E195124

UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1

Features

- Threaded C type
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast

Standard Finish

- Powder coat

Catalog Number	UPC	Size	Wire Size		Unit Carton	Ship Case	Weight/Case	A	B	C
			Max. Number	Max. Size						
C1	19900	1/2"	1	6 AWG	10	100	24	4.72	1.370	1.33
C2	19910	3/4"	2	6 AWG	10	50	21	5.57	1.625	1.54
C3	19920	1"	3	6 AWG	5	25	15	6.46	1.90	1.74
C4	19930	1-1/4"	3	2 AWG	2	10	15	8.528	2.77	2.49
C5	19940	1-1/2"	3	2 AWG	2	10	9	8.528	2.77	2.49
C6	19950	2"	3	2/O AWG	1	5	13	10.831	3.335	3.10
C7	19960	2-1/2"	3	4/O AWG	---	1	3	13.50	4.06	4.45
C8	19970	3"	3	250 MCM	---	1	6	13	4.685	4.45
C9	19980	3-1/2"	3	350 MCM	---	1	8	15.937	5.45	5.50
C10	19990	4"	4	350 MCM	---	1	8	15.937	5.45	5.50