

Rigid Conduit Bodies

Threaded T Type

Features

- Threaded T type
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications


- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast

Standard Finish

- Powder coat



Catalog Number	UPC	Size	Max. Number	Wire Size		Unit Carton	Ship Case	Weight/Case	Inches		
				Max. Size					A	B	C
T1	21730	1/2"	1	6 AWG		10	100	32	4.720	1.370	2.030
T2	21740	3/4"	2	6 AWG		10	50	26	5.570	1.625	2.335
T3	21750	1"	3	6 AWG		5	25	18	6.460	1.900	2.705
T4	21760	1-1/4"	3	2 AWG		2	10	17	8.528	2.770	3.630
T5	21770	1-1/2"	3	2 AWG		2	10	19	8.528	2.770	3.630
T6	21780	2"	3	2/0 AWG	---	---	5	7	10.831	3.335	3.980
T7	21790	2-1/2"	3	4/0 AWG	---	---	1	7	13.500	4.060	5.825
T8	21800	3"	3	250 MCM	---	---	1	7	13.000	4.685	5.825
T9	21810	3-1/2"	3	350 MCM	---	---	1	9	15.937	5.450	7.060
T10	21820	4"	4	350 MCM	---	---	1	9	15.937	5.450	7.060