# 3000 SERIES
## FLUSH MOUNTING LEXAN® HOUSING PHOTOCONTROL



Flush Mounting
Model 3010

## APPLICATIONS

- Pole lanterns
- Lawn lighting
- Walkways

## SPECIFICATIONS

**ON/OFF:** Turn ON is 1 to 5fc. Turn OFF is 3 to 15fc.

**TIME DELAY:** ON and OFF.

**CELL:** Cadmium sulphide, conformal coated 1/2" diameter.

**CONTACTS:** Normally closed (the unit fails in the ON position).

**LEAD WIRES:** Three color coded, minimum 9" wire leads, #16AWG, rated for 105 °C.

**POWER CONSUMPTION:** Averages under 1 watt.

**TEMPERATURE RANGE:** -40 °F to +158 °F (-40 °C to +70 °F).

**FAIL MODE:** ON.

**WARRANTY:** 5 years.

## FEATURES

**SENSOR:** Conformal coated cadmium sulphide photocell resists effects of moisture and airborne contaminants. Photocell responds to the light spectrum near to that of a human eye.

**OPERATION:** Delay of up to two minutes to prevent false switching due to light from passing vehicles, lightning, etc.

**STANDARDS:** Meets ANSI/UL773A.

**HOUSING & MOUNTING:** Control housing is weather-resistant molded Lexan® with ultrasonically welded seams.
MODEL 3000: Flush mounting through .6875" hole in post lantern or lighting fixture, ⅜" NPT, stem ¾" long. Gasket and nut supplied.
MODEL 3010: flush mounting into standard, raintight junction box. Includes aluminum plate and gasket to fit FS type outdoor junction box.

**ENERGY SAVINGS:** Works with screw base CFLs.

| CAT. NO. | UPC CODE | VOLTAGE (VAC) 50-60Hz | RATING | | LED |
|---|---|---|---|---|---|
| | | | TUNGSTEN | BALLAST | |
| 3000 | 60020 | 120 | 2000W | 1800VA | 600VA |
| 3002 | 60019 | 208-277 | 3470-4620W | 2080-2770VA | 1040-1385VA |
| NEW! 3006 | 60026 | 347 | 5760W | 3470VA | - |
| 3010 | 60021 | 120 | 2000W | 1800VA | 600VA |

*CSA certified only.

